AIRTAP HAND DRYER 371

110 V with IR sensor **Deck-mounted** Stainless Steel with satin finish 2-year warranty







AirTap features a minimalist, modern design in stainless steel with satin finish. The intelligent temperature control technology detects the room temperature and adjusts the heating element.

Technical data

| Туре | AIRTAP HAND DRYER |
|-----------------------------|---|
| | Prod. No.: 371 |
| | Touch-less warm-air hand dryer with IR sensor |
| | • |
| Dimension tap | H: 6.69" x W: 1.96" x D: 8.66" |
| Dimension motor | H: 7.99" x W: 12.04" x D: 5.90" |
| Material | Stainless steel, satin finish |
| Drying cycle | 10-15 sec. |
| Connection | 110 V, 50/60 Hz, Class I 🖶 |
| Total wattage | 600-1000 W |
| Heating element | 100-500 W |
| Motor | 500 W |
| Noise level | 68,5-70,5 dBA |
| Max. air capacity | 84-101 m/sec |
| Max. air outlet temperature | 134.6 F |
| Net weight | 13.22 lb |
| IP rating | IP35 |
| Tender text | Touch-less hand dryer in stainless steel with satin finish for deck mounting. Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP35, 110 V, 50/60 Hz, 1000 W, Class I (earthed). 68.5-70.5 dBA. Net weight: 13.22 lb. H: 6.69" x W: 1.96" x D: 8.66" |





Application

AirTap is a powerful hand dryer suitable for toilet rooms with a high visitor frequency. With its elegant slim design, the hand dryer is the perfect choice for all kinds of commercial washrooms. The range is an ideal build-in solution for construction projects and automatic hand wash stations.

References

Shopping centres, restaurants, hotels, airports, sports facilities, schools and public institutions.

Standard colour

Stainless steel, satin finish.

Activation

Infrared sensor and electronic timer. Touchfree. Activation distance adjustable 5.11" (± 0.78"). Automatic stop after 60 seconds of continuous use.

Motor type

Commutator motor with carbon brushes. 22,000-29,000 revolutions/min.

Protection

Automatic thermal cut-out in both motor and heating element.

Installation

Machine intended for table top mounting. Connection to fixed installation or via circuitbreaker. Installation must be carried out by a qualified electrician.

Approval









