

# BJÖRK BABY CHANGING STATION WITH SAFETY STRAP

## 3220/3222/3224

Wall mounted  
Powder coated aluminium  
2-year warranty



The BJÖRK baby changing station by DAN DRYER has been awarded several prestigious design prizes. Perfectly adapted ergonomically, it provides a comfortable and secure base for the infant, and with its design approach marked by purism and practical use, it goes far beyond familiar forms by creating a highly refined aesthetic. The baby changing station meets the highest demands, offering a great deal of comfort for both infants and parents. This product is SGS certified, compliant with the American standard ASTM F2285-04 and the European EN 12221-. It also meets ADA regulations when installed according to ADA guidelines.



### Technical data

Metric

Imperial

Type	Metric	Imperial
	<b>BJÖRK</b> Prod. No.: 3220, 3222, 3224  Baby changing station with safety strap	<b>BJÖRK</b> Prod. No.: 3220, 3222, 3224  Baby changing station with safety strap
<b>Width</b>	552 mm	21.73"
<b>Depth (folded up)</b>	100 mm	3.93"
<b>Depth (folded down)</b>	751 mm	29.56"
<b>Height (folded up)</b>	771 mm	30.35"
<b>Height (folded down)</b>	322 mm	12.67"
<b>Changing surface</b>	L: 700 mm x B: 510 mm	L 27.55" x W 20.07"
<b>Load capacity</b>	80 kg	176.37 lb
<b>Recommended working height</b>	950 mm above floor	37.40" above floor
<b>Force required to open</b>	~25 N; to close: ~25 N	~25 N; to close: ~25 N
<b>Net weight</b>	17 kg	37.47 lb
<b>Tender text</b>	Baby changing station. Powder coated steel wall unit, powder coated aluminum profile and electro-galvanized steel axle and levers. Load capacity: 80 kg. Net weight: 17 kg.	Baby changing station. Powder coated steel wall unit, powder coated aluminum profile and electro-galvanized steel axle and levers. Load capacity: 176.37 lb. Net weight: 37.47 lb.

### Application

BJÖRK, a true breakthrough in commercial bathroom products. The elegant design line is suitable for all types of public toilets.

### References

Offices and administration, shopping malls, restaurants, hotels, airports, sports facilities and public swimming pools, schools, public institutions and cultural centres.

### Standard colour

Prod. No. 3200: RAL 9003, white, gloss 75.  
Prod. No. 3205: RAL 9005, black, gloss 7-12.  
Prod. No. 3210: RAL Classic colours.

### Materials

Changing surface: Powder coated aluminium profile.  
Wall unit: Powder coated steel plate.  
Axle and levers: Electro-galvanized steel.

### Installation

Wall mounting. The recommended working height above floor: Approx. 950 mm / 37.40".

### Function

Torsion springs ensure the smooth and easy opening and closing motion of the unit.

### Certification

- EN 45545-2, HL3
- EN 12221-1 + A1
- TÜV Nord Certification
- DS/EN 61373:2010
- EN 71-3:2013 + A1:2004
- American standard ASTM F2285-04.

