BUILD-IN DISPENSER

871/872/873

IR-sensor Installation behind mirror or in cabinet Stainless steel 2-year warranty

Touch-free disinfection dispenser for liquid soap, disinfectant gel/disinfection spray/foam soap and foam disinfectant is specially designed for installation behind mirrors or in cabinets. The container is easy to refill from the top.





Technical data

Туре	BUILD-IN DISPENSER Prod. No.: 871/872/873	BUILD-IN DISPENSER Prod. No.: 871/872/873
	Build-in dispenser	Build-in dispenser
Dimensions without container	H: 200 mm x L: 111 mm x D: 101 mm	H: 8.23" x W: 4.37" x D: 3.97"
Dimensions with container	H: 210 mm x L: 111 mm x D: 101 mm	H: 8.26" x W: 4.37" x D: 3.97"
Material	Stainless steel	Stainless steel
Battery operated	4 x 1.5 V alkaline batteries type AA	4 x 1.5 V alkaline batteries type AA
Alimentation	Can be wired via a 6 V transformer	Can be wired via a 6 V transformer
Viscosity	871: For liquid soap and disinfectant gel: Viscosity 1-3000 cP	871: For liquid soap and disinfectant gel: Viscosity 1-3000 cP
	872: For disinfection spray: Viscosity 1 cP	872: For disinfection spray: Viscosity 1 cP
	873: For foam soap and foam disinfection gel Viscosity 1 cP	873: For foam soap and foam disinfection gel Viscosity 1 cP
Capacity	500 ml = 470 - 570 dosages	0.13 gal = 470-570 dosages
Net weight	0,95 kg	2.09 lbs
Tender text	Touch-free disinfection dispenser for build-in solutions. Capacity: 500 ml. Net weight: 0,95 kg. H: 210 mm x L: 111 mm x D: 101 mm	Touch-free disinfection dispenser for build-in solutions. Capacity: 0.13 gal. Net weight: 2.09 lbs. H: 8.26" x W: 4.37" x D: 3.97"

Application

Hygienic and durable automatic dispenser that is suited for all types of commercial restrooms. Specially developed for public toilets where there is a need for a built-in solution. The dispenser is virtually maintenance-free and can withstand frequent and often rough use.

References

Customised solution designed for use behind mirrors or in cabinets. Suitable for offices and administration, shopping centers, restaurants, hotels, airports, sports facilities and swimming pools, schools, public institutions, and cultural centers.

Installation

Wall mounting - behind mirror or in cabinet.

Details

Automatic activation distance 100 ± 20 mm. User-friendly LED light indicates when the dispenser is in operation.

Dispensing occurs when a hand is placed under the dispensing nozzle - dispensing only happens once per activation.

Compliance







